

SAFETY DATA SHEET

DOTP

CAS N° 6422-86-2

PAGE 1

Section 1 - PRODUCT SPECIFICATIONS

- DOTP is the phtalate-free plasticizer. It is excellent general purpose plasticizaer for flexible PVC.
- DOTP is the equal to or better than the other general purpose of phyhalate plasticizars.
- It has good mechanical and permance propperties and low temperature flexibility. It also provides low viscosity in plastisols with good viscosity stability. PLASTSOFT has good compatibility with polyvinyl chloride, polystyrene, cellulose, nitrate, methylcellulose, polymethyl, methacrylate, major polymers and reins. It can be used in medical applications including tubing films, bags, gloves, clinderen toys, childcare article, food contact materials, strech film, cable and wires, artificial leather. It is widely available and tested. and has a comprehensive toxicological portfolip, which indicates that it can be used in toys, beverage packaging and medical devices.

Section 2 - Properties

PARAMETER	VALUE ////	METHOD
MOLECULAR WEIGHT g/mo	ol 390	
ESTER CONTENT Min	99.50	ASTM D3465
APPERANCE	Clear Liquid	ASTM D 4176
ODOR	Characte <mark>r</mark> istic///////	ASTM D 1296
COLOUR. Hazen. MAX	30 ////////////////////////////////////	ASTM D1209
ACIDITY (Mg, KOH/g) Max	0.1 ////////////////////////////////////	ASTM D 974
REFRACTIVE INDEX. 20C	1. <mark>4</mark> 89/+ 0.003////	ASTM D 1747
SPECIFIC GRAVITY .20C	0.983 ÷ 0.002gr/ cm3	ASTM D 1298
FLASH POINT	//>/218°C////	ASTM D 92
WATER CONTENT Max %	////0.05/////	ASTM D 1364
VISCOTY. cp ' 25°C	////60-68///	BROOKFIELD
VISCOTY. cp 20°C	78-90	
FREE ALCOHOL Max %	0.1	GC/MS
	((((()))))	